


折弯示意图  
展开出货



LED CIRCUIT DIAGRAM:

If=40mA Vf=2.8-3.3V

PIN	DESCRIPTION
1	GND
2	LEDK
3	LEDA
4	VDD
5	GND
6	GND
7	D/C
8	CS
9	SCL
10	SDA
11	RESET
12	GND

NOTES:

1. GENERAL TOLERANCE:  $\pm 0.2$
2. ( ) REFERENCE DIMENSION
3. Important dimension: ①~⑦

LCD Type	0.99\" TFT, Transmissive Normally black, IPS
Resolution	128(RGB)*115
View Direction	All o'clock
LCD driver IC	GC9107
Color depth	262K
Interface types	4 SPI
Operating voltage	3.3V
With TP/Lens	without
Backlight	1 LED, 40mA (typ), 3.0V (ref.)
Surface luminance	350 cd/m <sup>2</sup> (typ)
Operating temperature	-10°C~60°C
Storage temperature	-20°C~70°C
Color chromaticity	[white] x/y.

版本 (Version)	变更记录 (Revise History)	日期 (Date)
A0	Initial release	2023.08.02

设计 (DESIGN)	San
审核 (CHECKED)	Aron
批准 (APPROVED)	Aron
客户承认 (CUSTOMER APPROVAL)	



TITLE: LCM	页面 (Page) 1 / 1
Drawing No. TST010QQBG-05	单位 (Unit) mm
	比例 (SCALE) 1 : 1
	角度 (Angle) $\odot$